

PTO BUNKER AUGER



4 Directional Spout Control

Low Profile Hopper

Cost effective option for filling grain bunkers up to 38m wide

- Parallel bunker repositioning in less than 2 minutes
- Large full width triple flight drive over hopper
- Electric directional spout control
- PTO Drive
- Hydraulic folding ramps & lift (raises & lowers wheels)
- Optional barrel lengths to suit bunkers up to 38m wide
- Up to 340 tonne/hr constant flow
- Simple operation by receival personnel & delivery drivers



www.grainline.com.au | 1800 810 498

PTO BUNKER AUGER SPECS

Size	15 inch diameter, with a 15, 18 or 21 metre barrel including swivel spout & lights
Tractor Requirements	180-200 Horsepower
Operating Speed	540 Flight RPM on a 1-1.85 Ratio Gear Box = 1,000 PTO Tractor Required 540 Flight RPM on a 1-1 Ratio Gear Box = 540 PTO Tractor Required
Bunker Size	Suits up to 38m wide bunker
Hopper	3.5m x 1.5m x 300mm Low Profile Triple Flighted Hopper
Hopper/Transfer Flight/ Auger	3 x 8" Hopper Flight 2 x 10" Transfer Flight 2 x 12" Lift/Incline Flight 1 x 15" Auger Flight
Auger Capacity	Up to 340 tonne/hr (wheat)
Ramps	4.2 m x 3.5 m Hydraulic Folding, Including Bi-Folding Extensions (ramp height 300mm, easily negotiated by trucks & drivers)
Auger Barrel	15 inches (380mm), 3mm with Rotatable Barrel
Flighting	355mm x 355mm x 4.8mm with 80nb (88.9 mm) Bore
Finish	Grainline Blue 2-pac paint with Powder Coated Ramps
Operating Angle	27 degrees
Spout Movement	Electric Spout Movement
Warranty	12 months

